



SPVC-101

EXTRUDED

PVC INSULATED SLEEVE 90°C



FEATURES

- ✓ Max. Temp. Up to 90°C
- ✓ Good Thermal Stability.
- ✓ Good Tensile Strength & Elongation.
- ✓ Good Flexibility.
- ✓ Excellent Abrasion Resistance.
- ✓ Resist against many solvent, oils, and concentrated acids.
- ✓ Economical
- ✓ Outstanding Electrical Properties

AVAILABLE OPTIONS

- ✓ SS Wire Covering
- ✓ Available in Different Color
- ✓ Available with different wall thickness as well as voltage Grade.
- ✓ Available with flame retardant & Low smoke properties.
- ✓ Available with Heat Resisting Properties.

EXTRUDED PVC INSULATED SLEEVE

S.No.	Size in (mm)	Inner Dia (mm)	Wall Thickness (mm)	Max. Outer Dia (in mm)	Approx Weight (gm/mtr)
SPVC101	1.5	1.5	0.6	2.7	6.3
SPVC102	2	12	0.6	3.2	7.6
SPVC103	2.5	2.5	0.8	4.1	12.9
SPVC104	3	3	0.8	4.6	15.0
SPVC105	4	4	1	6	25.2
SPVC106	6	6	1	8	33.9
SPVC107	8	8	1.2	10.4	56.2
SPVC108	10	10	1.4	12.8	80.3
SPVC109	12	12	1.6	15.2	108.3
SPVC110	14	14	1.6	17.2	124.5
SPVC111	16	16	1.8	19.6	158.5

ORDERING CODE

Conductor Size

(SPVCXXX)

101
to
111

Color Code

(XX)

RE
YE
BR
BL
BK
GR
PU
OR
WH
GN

Note : RE - (Red), YE - (Yellow), BR - (Brown), BL - (Blue), BK - (Black), GR - (Grey), PU - (Purple), OR - (Orange), WH - (White), GN - (Green)