



SFIB-101

BRAIDED

FIBER GLASS INSULATED SLEEVE 400°C



- ✓ Max. Temp. Up to 400°C
- ✓ Excellent Heat Resistant.
- ✓ Excellent Flexibility.
- ✓ Silicon Insulated Varnish at outer.
- ✓ Good Strength.
- ✓ Resist against many solvent, oils, and concentrated acids.
- ✓ Outstanding Electrical Properties

- ✓ Available in White & Black Color
- ✓ Available with different wall thickness as well as voltage Grade.

BRAIDED FIBRE GLASS INSULATED SLEEVE

S.No.	Size in (mm)	Inner Dia (mm)	Wall Thickness (mm)	Max. Outer Dia (in mm)	Approx Weight (gm/mtr)
SFIB101	1.5	1.5	0.20	1.90	3.00
SFIB102	2.0	5	0.30	2.60	5.00
SFIB103	3.0	3.0	0.35	3.70	7.50
SFIB104	6.0	6.0	0.40	6.80	15.00
SFIB105	12.0	12.0	0.60	13.20	40.00
SFIB106	15.0	15.0	0.60	16.20	48.00
SFIB107	16.0	16.0	0.65	17.30	52.00

ORDERING CODE

Conductor
Size

(SFIBXXX)

101
to
107

Color Code

(XX)

BK
WH

Note : BK - (Black), WH - (White)